LVIS IceBridge Greenland and Antarctica Data

Bryan Blair

NASA Goddard Space Flight Center, Greenbelt, Maryland
Bryan.Blair@nasa.gov

Michelle Hofton

Department of Geography, University of Maryland, College Park mhofton@umd.edu

David Rabine, Scott Luthcke, Colleen McIntosh

NASA Goddard Space Flight Center, Greenbelt, Maryland






NASA's Land, Vegetation and Ice Sensor (LVIS)



- NASA's Land, Vegetation and Ice Sensor (LVIS) is a medium-altitude (10km), medium-footprint (5-25m) Waveform-Digitizing Lidar.
 - Measures surface topography and topographic extent (e.g., crevasse depth), and structure for every footprint.
 - Digitally records the shape of each outgoing and returning laser pulse (waveform).
 - Nominal mode: 20m footprint/2km swath from 10km above ground.
 - ❖ 500-5,000 Hz laser repetition rate.
 - ❖ 1064nm wavelength, 8 ns (FWHM) laser pulse.
 - Nadir-stabilization maximizes coverage.





Sensor installed in NOAA Cessna Citation II





LVIS Lidar Remote Sensing of Greenland, 2009



- In April 2009, LVIS imaged areas of Greenland for IceBridge
 - → 3 x ~8-hr flights in NASA P-3B aircraft
 - Based out of Thule
 - → ~25m wide footprints, 1.5-2km swath
 - Altitude: 25,000-27,000'
 - ~30 million waveforms collected




- LVIS Lidar accurately maps surface topography and measures surface vertical and spatial structure across multiple scales
- The data form the basis for future repeat surveys of the ice sheet and its margins from aircraft during the data gap between the current orbital ICESat and future lidar missions.



LVIS Measurement Process





Data products include:

- "Ground" elevation: zg (elevation using center of lowest mode)
- Elevation of highest reflection: zt
- Vertical distribution of intercepted surfaces (waveform).
- Vertical extent (e.g., feature depth or height): RH100
- Energy quartiles (RH25/50/75)
- Other products ?: -waveform centroid-ICESat


Data available at https://lvis.gsfc.nasa.gov

- The waveform represents the entire time history of interaction between the laser pulse and the surface of the Earth.
- >Allows extraction of multiple data products, and to apply, reapply algorithms.



LVIS Data Available Online






LVIS data products are available to download from <u>https://lvis.gsfc.nasa.gov</u>

Currently >500 registered users worldwide

Latest data products
distributed online as
they become available

- Web site also contains useful information on using LVIS data
- Users can ask LVIS-specific questions if they have problems
- Frequentlyupdated FAQ section







Example Ice Waveforms



Surface roughness or texture is quite Varied depending on the surface conditions.

This is captured by the return waveform. Capturing the entire waveform also allows for future reprocessing with improved algorithms.








Change Detection with Waveforms








Data collected in Greenland in 2009



- ❖ ~9,500 lineal km of ICEsat tracks imaged, including 1,500 lineal km imaged previously using LVIS in 2007.
- Flights timed with ICESat overpass to minimizing biases due to change
- LVIS swaths cover a wide variety of terrain, change regime areas, and include ATM profiles
- The LVIS data set provides a consistent datum to enable inter-mission calibration and validation, and assist in the separation of inter-mission observational system biases and errors from true decadal and seasonal surface elevation change.






Data Precision, Greenland 2009



- Compare coincident LVIS data to assess data precision
 - → Footprint centers < 1m of each other</p>



Elevation Difference between Coincident Footprints (m)


Flight	#1	#2	#1 vs #2
Mean difference (m)	0.00	0.00	0.02
Standard deviation (m)	0.06	0.07	0.07




Data Accuracy, Greenland 2009



- Using differential kinematic GPS data from Thule ramp
 - Courtesy of E. Frederick (NASA ATM)
- LVIS elevations compared to closest GPS measurement
- 290 comparison points
- Standard deviation $(1\sigma) = 0.065 \text{ m}$



LVIS minus Ground GPS (m)







LVIS Performance in Greenland, 2007







Horizontal Positioning Accuracy:




Northing (m)

Small footprint and LVIS data positioned within 0.4m

- LVIS data collected on 9/20/07 and 9/21/07 from ~27,000' in P3-B.
- Two ~850km long transects over ice sheet plus ~35 km long transect in the Summit area.
- Elevations differences between coincident footprints used to evaluate system performance.

From: Hofton et al. (2008), Geophysical Research Letters, DOI:10.1029/2008GL035774







Waveform Lidar Elevation Accuracy, 2007



- Using differential kinematic GPS data from Sondrestrom (Kangerlussuaq) runway and ramp area
 - Courtesy E. Frederick (NASA ATM)
- Single overflight on 9/20/07
- LVIS elevations compared to closest GPS measurement








Standard deviation (1 σ): 0.07 m



2009 LVIS: Comparison to ICESAT








2009 LVIS: Comparison to ICESat








2009 LVIS: Comparison to ICESat






Elevation change LVIS 2009 to Icesat



LVIS Northern Sea Ice Flight April 16 2009







Status of Greenland 2009 Data





- 3 LVIS flights: 2 land ice and 1 sea ice
- ~9 million waveforms (after quality checks) collected on each flight (~30 million total)
- Data processing completed on land ice flights and data released on lvis web site.
- Preliminary processing only on sea ice flight problem due to power supply failure on LVIS Applanix 510. Data quality reduced. Some success using separate data segments (before and after Applanix dropout). Attempting to use Ames Applanix 610 data but unit was mounted several meters away on ATM long lever arm and potential airframe flexing will result in some degradation in performance.
- Expect to release preliminary sea ice data by next week.



LVIS Flights Antarctica 2009











LVIS Peninsula Flight – Crane Glacier







Four ICESat-1 profiles cross the Crane Glacier and intersect with ATM 'along-flow' profiles that were initially taken in late 2002 and 2004. Those intersections have enabled the timing of elevation changes at those locations to be determined. Note, Track 0129 now crosses the Crane Fjord which once contained ice >700 m thick. Based on the Nov. 2009 ice edge (red curve) and the late 1990s grounding line, the Lower Crane (fjord) has lost ~20 cubic km of ice.



Pine Island and Pole Hole


-100000.0



 Pole Hole Flight covered ~100% of desired area (good weather call Seelye) and sampled ~half a million ICESat footprints. ~40% of all ICESat data orbits.

 Some Pine Island data losses inland due to clouds.









Preliminary Data Precision, Antarctica 2009



Assessing elevation differences between coincident LVIS footprints





Elevation difference between coincident footprints (m)

Mean difference: 0.01m Standard deviation (1σ): 0.23m

Mean difference: 0.05m Standard deviation (1σ): 0.15m

 Note: These preliminary results use an initial (intermediate) parameter solution based on PPP trajectories (i.e., no base stations) and preliminary waveform processing.




Preliminary Data Accuracy, Antarctica 2009



- Using differential kinematic GPS data from Punta Arenas airport parking lot
- LVIS elevations compared to closest GPS measurement
- 82 comparison points
- Mean = 0.003m
- Standard deviation $(1\sigma) = 0.04m$
- Only Crane flight calibration pass has been analyzed so far.

LVIS minus Ground GPS (m)








Comparison to Aster



LVIS minus ASTER Global DEM over Crane Glacier









Status of LVIS Antarctic 2009 Data



- No funding for processing these data has been received.
 - Lack of stable funding prevents us from hiring small team has conflicts between deployments and data processing, and other research.
- After funding is received we should be able to release a 1st draft DEM of the Antarctic Peninsula data in weeks.
- Other 2 high-altitude LVIS flights (Pine Island, Pole Hole)
 - Beginning work on better quality GPS trajectories
 - GPS/Gyro lever arm calculations in process
- Work to incorporate Applanix 610 data has not yet begun
 - **◆** Should result in ~2X better accuracy over sloped terrain.
- Collaborating with UNAVCO and NSIDC on LVIS data formats - LVIS/ICESat data proposal funded.